

Perimeter LED Light

CSL1109

The Perimeter Light utilises the latest advancements in patented LED technology to provide the highest quality of uniformly distributed light combined with substantial energy savings of typically 60%. These lights are ideally suited for external usage for all exercises yards, secure carparks, perimeter fencing or walk way applications. Best suited to heights of 4 - 6.5 metres.

Specification

- Efficiency: Typically uses over 60% less energy than fittings such as sodium or metal halides.
- Zero Maintenance: Reducing costs and the disruption caused by routine maintenance.
- An estimated lifetime of over 60,000 hours.
- Glare-free, uniformly distributed light output, achieving LG Standards Lux levels.
- Operates voltages between 100-277 Volts AC.
- IP66 rated for external application.
- Universal bracket to pole mount or fit to T-Bars, the unit is also available as a twin unit (pictured).
- Single unit size is 340 x 210 x 135mm.
- 5 Years Warranty.



Twin Unit Perimeter Light

Finish

- Metallic with a polycarbonate facia.

Linear Surface Mounted Light

CSL1110

Impact-resistant ceiling mounted Linear light. These lights are ideally suited for enclosed walkways / corridors.


Specification

- Available in 1, 2 or 3 x T5 28w or 54w lamps.
- Emergency 3 hours optional (28w & 38w only).
- Operates voltages between 100-277 Volts AC.
- IP54 rated and IK10+ impact tested.
- This product may only be ceiling-mounted.
- Lamp not included.
- 1 Years Warranty.



Finish

- 1.6mm steel back-plate.
- 5mm UV stabilized opal textured polycarbonate lens.



Safer Cell Surface Mounted Light

CSL1111

Impact-resistant ceiling or wall mounted light. These lights have been designed to be ligature resisting, very robust and secure. Ideal to be used in high risk areas.

Specification

- Available in 1, 2 or 3 x T5 14w or 24w lamps.
- Impact-resistant polycarbonate lens.
- Emergency 3 hours optional.
- Operates voltages between 100-277 Volts AC.
- IP65 rated and IK10+ impact tested.
- Lamp not included.
- 1 Years Warranty.



Finish

- 1.6mm steel back-plate.
- 5 - 8mm UV stabilized frosted / opal textured polycarbonate lens.

