CellSecurity.co.uk

custodial and detention solutions

Washroom Accessories

SECTION 10

CSL1010

10

SECTION 10

Semi Recessed Velocity Dryer

Specification

- High quality stainless steel (304 grade).
- Auto resetting thermostat.
- 1600w Dryer / 350-700w motor (adjustable) / 450-900w heating element (adjustable).
- Automatic infra-red sensor. •
- Dries hands in less than 10 seconds. •
- Auto shut off in 60 seconds.
- Air output at 100m/second (adjustable).
- Splash proof: IPx1.
- Very small projection. •
- Low energy usage reduces power consumption by up to 70%.

Finish

Satin Stainless Steel. ٠

Size

H 513mm x W 250mm x D 62mm (Recess dimensions H 495mm x W 235mm x D 122mm).

Specification

- High quality stainless steel (304 grade).
- To be used in conjunction with a disabled toilet pan.
- Consists of padded back rest, one hinged support rail and three rails.
- Concealed fixings.

Finish

Satin Stainless Steel.

Size

- Backrest 450mm projection.
- Grab rails 600mm in length.
- Hinged support 750mm in length.

Baby Changing Units

Doc M Pack

Specification

- Entire body is 16 gauge type 304 stainless steel
- Full stainless steel frame and hinges provide maximum durability
- Concealed pneumatic control cylinder provides smooth opening/closing
- Supports a static load of 181kg
- Surface mounted to wall.

Finish

Satin stainless steel

Size

- CSL1012A H 903mm x W 590mm x Open 876mm / Closed 120mm
- CSL1012B H 607mm x W 920mm x Open 545mm / Closed 100mm









Baby Changing Unit



CSL1012B **Baby Changing Unit**





CSL1012

CSL1011