

## CSL1101

## Full Length Cornice LED Light

The full length cell cornice LED light utilises the latest advancements in patented LED technology to provide the highest quality of uniformly distributed light combined with substantial energy savings of typically 60%. These lights have been designed to be ligature resisting, very robust and secure. Ideal to be used in high risk areas.



**CSL1101CCTV**  
CCTV Housing

**Specification**

- Suitable for installation within cells and corridors.
- Full length cornice light is available for lengths from 1380mm to 3000mm (single unit).
- Available in many different combinations to suit the application.
- Three light levels can be incorporated (500,300,15 lux).
- Emergency backup available (battery 3 hours / voltage input)
- Home Office Approved.
- IP65 & IK10+ rated.
- 14 years maintenance free life (based on 12 hours a day usage).
- Efficiency: Typically uses over 60% less energy than traditional fluorescent fittings.
- Zero Maintenance: Reducing costs and the disruption caused by routine maintenance.
- An estimated lifetime of over 60,000 hours.
- Glare-free, uniformly distributed light output, achieving LG Standards Lux levels.
- Operates voltages between 100-277 Volts AC.
- LED Type Phillips Rebel (ES) 3000k - 4500k as standard (other colour temperatures available).
- Ceiling to wall mounted through the main body.
- When Hard pick mastic is applied to outer body you can still service the light if required.
- 5 Years Warranty.

**Finish**

- Metallic with a polycarbonate facia.

**Options**

- Cut to suit various different lengths.
- CCTV Blank and populated housings available which allows full room coverage.
- Ventilation grills.
- Smoke detectors.
- Bespoke fitments available upon request.

CSL1101A	Single operation (on / off) LED tray
CSL1101B	Twin operation (on / off / night light) LED tray
CSL1101C	Triple operation (high level / on / off / night light) LED tray
CSL1101xA	Emergency AC backup
CSL1101xB	Emergency 3 hour battery backup
CSL1101D	Main Body Assembly - 3000mm (cut to suit on site)
CSL1101E	End Cap Assembly short - 155mm (cut to suit on site)
CSL1101F	End Cap Assembly long - 340mm (cut to suit on site)
CSL1101G	Joining Plate - 85mm
CSL1101H	Viewable Panel - 1210mm (LED light cover)
CSL1101I	Viewable Panel - 655mm
CSL1101J	Viewable Panel - 470mm
CSL1101K	Viewable Panel - 285mm
CSL1101L	Blank Panel - 1210mm
CSL1101M	Blank Panel - 1025mm
CSL1101N	Blank Panel - 840mm
CSL1101O	Blank Panel - 655mm
CSL1101P	Blank Panel - 470mm
CSL1101Q	Blank Panel - 285mm
CSL1101CCTV-B	Housing Blank - 200mm
CSL1101CCTV-S	Housing with Standard Camera - 200mm
CSL1101CCTV-I	CCTV Housing with IP Camera - 200mm