

CSL1311



Ultimate 3000 - MIO Expansion Card

The MIO Card enables the 3000 range of exchanges to collect inputs for personnel and general alarms including the control of doors, barriers, motorised gates and outputs to control and monitor auxiliary systems, specifically when the exchange is connected to the Genesys Frontend. (CSL1301).

Specification

- Digital input and output.
- 8 Balanced inputs for high security installations.
- 2 x reed relays outputs (max 100ma load) and 2 x 5 amp voltage free relays.

CSL1312

Affray Strip



A continuous switch / alarm manufactured in a low profile minimise unintentional activations whilst the large target area ensure ease of activation in event of an emergency.

Specification

- Ease of activation – target area 60% of the exposed face of switch.
- Tamper Proof installation – built in security features to ensure integrity of the switch.
- Wide operating temperature range 4 to 40 degrees centigrade.
- Colour Options Red, Green & Blue supplied as standard.
- Inherent shape retention – reinforces operational properties of switch.
- Illumination option – provides feedback on operational status to Staff.
- Quick & easy to install - Cut on site to suit requirements.
- Pre-wired fittings.
- Self aligning components.
- Range of ABS fittings.
- Easy to integrate in to propriety systems.
- IP65 rated.



endcap secured with tamperproof fixings

