### CellSecurity.co.uk

custodial and detention solutions

### Sanitary Ware

CSL0971

CSL0972

SECTION 9

### Non Concussive Basin Time Flow Taps

### Specification

- Functions for a period of time and then closes automatically. •
- Non concussive operation.
- Variable time flow.
- Max. Operating pressure 10 bar.
- Min. Operating pressure 0.5 bar.
- Max. Inlet Temperature 65°C.
- Timed flow (Standard) 15 seconds at 1 Bar.
- 1/2" BSP thread. •

#### Finish

Chrome Plated with brass body. •



supplied as a pair

# Non Concussive Wall Mounted Push Taps

#### Specification

- Functions for a period of time and then closes automatically.
- Non concussive operation.
- Variable time flow.
- Max. Operating pressure 10 bar.
- Min. Operating pressure 0.5 bar.
- Max. Inlet Temperature 65°C.
- Timed flow (Standard) 15 seconds at 1 Bar.

Ideal for those with limited dexterity.

Max. Operating Pressure 10 bar.

Min. Operating Pressure 0.2 bar.

Max. Inlet Temperature 85°C. Max. Basin Thickness 26mm.

- 1/2" BSP thread.
- WRAS Approved. •

#### Finish

•

•

•

•

Finish

Specification

1/4 turn cartridge.

1/2" BSP thread.

High polished chrome.

High polished chrome brass body.



supplied as a pair

## Lever Taps

# CSL0973





supplied as a pair

## Anti-Vandal Bubbler

CSL0974B

SANITARY WARE



#### Specification

CSL0974A - Can be used either as a fountain or tap dependant on angle.

Easy to grip handle operated by either hand or wrist.

- CSL0974B Horizontal or vertical mounted tap.
- Ligature resisting unique design.
- Hygienic and easily cleaned.
- Proven long term product life.
- 1/2 BSP thread.

### Finish

High polished chrome.





CSL0974A