CSL1112

Bulkhead Square 2D Light

Impact-resistant ceiling mounted 2D light. These lights are ideally suited for enclosed walkways / corridors.


SECTION 11

Specification

- Available in 16w, 28w, 38w, 55w 2D.
- Impact-resistant lens.
- Emergency 3 hours optional (28w & 38w only).
- Operates voltages between 100-277 Volts AC.
- IP54 rated and IK10+ impact tested.
- This product may only be ceiling-mounted.
- Lamp not included. 1 Years Warranty.

Finish

- 1.6mm steel back-plate.
- 5mm UV stabilized opal textured polycarbonate lens.



CSL1113

Safer Cell Circular 2D Light

Impact-resistant ceiling or wall mounted light. These lights have been designed to be ligature resisting, very robust and secure. Ideal to be used in high risk areas.

Specification

- Available in 16w, 28w, 38w or 55w 2D.
- Impact-resistant polycarbonate lens.
- Emergency 3 hours optional (16w, 28w & 38w only).
- Operates voltages between 100-277 Volts AC.
- IP65 rated and IK10+ impact tested.
- Lamp not included.
- 1 Years Warranty.

124mm

Finish

- 1.6mm steel back-plate.
- 5 8mm UV stabilized frosted / opal textured polycarbonate lens.

