

## CSL1201

## Framed 360° Domed Polycarbonate Mirror

**CSL1201S (standard)**

450mm diameter  
(under 6m distance\*)

**CSL1201L (large)**

600mm diameter  
(over 6m distance\*)

\* This is the combined distance from the observer to the mirror PLUS the distance from the mirror to the object being observed.

**Specification**


- Constructed from 3mm thick unbreakable polycarbonate with scratch resistant coating, the 360° hemisphere mirror is designed for mounting on the ceiling, thus providing 200° of vision from any direction.
- Foam backing block to prevent deformation of mirror.
- The mirror is secured in a steel flanged frame and fixed to the ceiling using tamper proof screws.

**Finish**

- Polyester powder coated frame.


**Options**

- Available in 450mm diameter (standard) or 600mm diameter (large).



## CSL1202

## Framed 180° Domed Polycarbonate Mirror

**CSL1202S (small)**

450mm x 225mm x 150mm  
(under 6m distance\*)

**CSL1202M (medium)**

600mm x 300mm x 160mm  
(under 9m distance\*)

**CSL1202L (large)**

900mm x 450mm x 165mm  
(over 9m distance\*)

\* This is the combined distance from the observer to the mirror PLUS the distance from the mirror to the object being observed.

**Specification**

- Constructed from 3mm thick unbreakable polycarbonate with scratch resistant coating, the 180° half hemisphere mirror is designed for mounting at high level, at the junction of the wall and ceiling, thus providing a wide angle view of the room.
- Foam backing block to prevent deformation of mirror.
- The mirror is secured in a steel flanged frame and fixed to the ceiling / wall using tamper proof screws.
- Overall size is 600mm wide x 300mm high x 160mm deep. CSL1202M

**Finish**

- Polyester powder coated frame.

**Options**

- Available in 450mm diameter or 600mm diameter (standard) or 900mm diameter (large).

