Bedding

SECTION 16

CSL1601

T

CSL1601-50 50mm thickness

CSL1601-100 100mm thickness

CSL1601-150 150mm thickness

CSL1601-200 200mm thickness

NOTE - Please state size required when ordering

Date embossed for traceability.

Specification

erties.

Fire Resistant Mattress

• Tested to BS 7177: 2008 Ignition Source 7.

Fully welded seams for added security, hygiene and strength.

Fire resistant and vandal proof.

Finish

- Filling full depth fire resistant foam compatible with fire test standard BS 5852 Part 2 Ignition source 5.
- Covering wrinkle free rip stop mattress cover is constructed of fire resistant 650gsm PVC coated polyester. Complies to tear strength BS 3234 and fire resistant to BS 5438 Test 2A.

Tear resistant waterproof fabric cover with added rip stop, anti-bacterial and fungal prop-

Options

- General sizes are 1900 x 600mm OR 1900 x 750mm with a thickness of 50mm.
- 50, 100, 150 and 200mm mattress thickness available.
- Customs sizes are available to order.



DDA Mattress is typically 150 or 200mm thick

CSL01602

Pillow



Specification

- Fire resistant and vandal proof.
- Fully welded seams for added security, hygiene and strength.
- Tear resistant waterproof fabric cover with added rip stop, anti-bacterial and fungal properties.
- Size: 580 x 350 x 100mm.

Finish

- **Filling** full depth fire resistant foam compatible with fire test standard BS 5852 Part 2 Ignition source 5.
- Covering wrinkle free rip stop mattress cover is constructed of fire resistant 650gsm PVC coated polyester. Complies to tear strength BS 3234 and fire resistant to BS 5438 Test 2A.

CSL01603

Pillow Case



- Low cost item.
- Suitable for high risk areas.

Finish

100% flame resistant polyester.

Fire resistant to BS 5815 Part 3 and BS 5867 Part 2 Source 7.

CellSecurity.co.uk

custodial and detention solutions